





100 CFM/2.0 Sones @ 0.10" SP. 83 CFM @ 0.25" SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 11" x 133/4". Moonstone glass lens.

Blower Wheel

Balanced polymeric dual inlet blower wheel $5^{1/4}$ " dia. x $2^{7/8}$ " depth, 30 paddles, secured in place via press fit.

Motor

Enclosed 4 pole electronically balanced permanently split capacitor motor (PSC); life time lubricated, suitable for continuous operation. Motor bearings - ball. Rated 115/120 volts, 60 Hz.

Fan Housing

23 gauge galvanized steel housing. Overall dimensions $10^{7}/_{8}$ " x $9^{3}/_{8}$ " x $7^{7}/_{8}$ ".

Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area


For bathrooms up to 100 sq. ft. For other rooms up to 125 sq. ft.

• Electrical Connections

½" electrical knockouts provided. Easy wiring access via either internal or external wiring compartment cover.

Lighting

LED Lamp rated 6 Watt 450 Lumens 75 Lumens/Watt Night light = 20% of full brightness



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.



Unit Mounting

The housing will mount in ceilings with at least 8" of clearance and through drywall thickness up to $^{3}/_{4}$ ", with a rough-in opening of $11^{1}/_{8}$ " x $9^{5}/_{8}$ ". Rated for ceilings insulated to R-40. The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

Single Pack Shipping Info

Box Dim Box Dim: $14^{1}/_{8}$ " x $11^{5}/_{8}$ " x 12" Shipping Weight: 11.5 lbs.

EXPANDED PERFORMANCE												
									Sones	Fan Speed	Maximum	
		Static Pressure (inches of w.g.)							@ .1 SP	RPM	Fan Watts	Amps
		0	0.5	0.1	0.15	0.2	0.25	0.375				
Air Flow - C	FM	108	104	100	95	90	83	70	2.0	1182	26.5	0.60

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	









1.800.667.8721

Specifications subject to change without notice. Updated 8-1