

at

cabinet :: accessories
UNLIMITED



Detailed installation instructions are enclosed.

Tall Unit Pantry Pull-Outs for Diagonal Cabinets



Diagonal tall unit pantry pull-out

Minimum cabinet width 262 mm (10 1/4")
Minimum cabinet depth 495 mm (19 1/2")
Load capacity: 100 kg maximum (220 lbs.)

Support frame for diagonal pantry pull-out for tall units

Width: 25 mm (1")
Depth: 455 mm (18")
Finish: steel, plastic-coated

Min. inside cabinet height	Height of frame	white alum. RAL 9006	white RAL 9010
mm inch			
1235 48 5/8"	1165	546.78.211	546.78.711
1463 57 5/8"	1393	546.78.212	546.78.712
1780 70	1710	546.78.213	546.78.713
2080 82	2010	546.78.214	546.78.714

Packing: 1 pc.



Front bracket

Finish: steel, plastic-coated

Length	Angle	white alum. RAL 9006	white RAL 9010
300 mm	55°	546.78.222	546.78.722
355 mm	45°	546.78.221	546.78.721

Packing: 1 set (2 pcs.)



Pull-out slide

Partial-extension slide, complete with upper runner
Load capacity: 100 kg (220 lbs.)
Finish: steel, plastic-coated

color	Cat. No.
white aluminum, RAL 9006	546.78.200
white, RAL 9010	546.78.700

Packing: 1 pc.



Front stabilizer

Finish: steel, zinc-plated

Cat. No.	546.78.230
----------	------------

Packing: 1 pc.

inside cabinet height of 1235 mm = 1 pc.
inside cabinet height of 1463 mm = 2 pc.
inside cabinet height of 1780 mm = 3 pc.
inside cabinet height of 2080 mm = 3 pc.




Hanging wire baskets


size: 228 x 467 x 74 mm
(width x depth x height)
Finish: steel

for angle	chrome-plated white, RAL 9010	plastic-coated
55° right	545.60.226	545.60.726
left	545.60.235	545.60.735
45° right	545.60.224	545.60.724
left	545.60.234	545.60.734

Packing: 1 pc.



right hand cabinet



left hand cabinet

Dimensional data not binding.
We reserve the right to alter specifications without notice.