



# Linear Fixture Radiance Series

Flat Profile Linear Fixture




LED Tape Lighting  
**5 YEAR WARRANTY**

Accessories  
**3 YEAR WARRANTY**

**kitchensource.com**  
1.800.667.8721

## Single color output

- 3000K – Soft White
- 4000K – Cool White



## 007 Flat Profile Linear Fixture – 101 Lumens Per Foot

Part Number	Profile Type	Wall Cabinet Width	Fixture Dimensions	Watts per Fixture	Lumens Per Fixture	Kelvin Temp.
LR1P724V09-02WTemp	Flat 007 profile.	9"	4-11/16" x 5/8" x 3/8" (119 mm x 15 mm x 10 mm)	2	53	3000K (3) 4000K (4)
LR1P724V12-02WTemp	Flat 007 profile.	12"	8-5/8" x 5/8" x 3/8" (219 mm x 15 mm x 10 mm)	2	69	3000K (3) 4000K (4)
LR1P724V15-02WTemp	Flat 007 profile.	15"	12-9/16" x 5/8" x 3/8" (319 mm x 15 mm x 10 mm)	2	101	3000K (3) 4000K (4)
LR1P724V18-03WTemp	Flat 007 profile.	18"	12-9/16" x 5/8" x 3/8" (319 mm x 15 mm x 10 mm)	3	116	3000K (3) 4000K (4)
LR1P724V21-03WTemp	Flat 007 profile.	21"	16-1/2" x 5/8" x 3/8" (419 mm x 15 mm x 10 mm)	3	148	3000K (3) 4000K (4)
LR1P724V24-03WTemp	Flat 007 profile.	24"	20-7/16" x 5/8" x 3/8" (519 mm x 15 mm x 10 mm)	3	164	3000K (3) 4000K (4)
LR1P724V27-04WTemp	Flat 007 profile.	27"	24-3/8" x 5/8" x 3/8" (619 mm x 15 mm x 10 mm)	4	195	3000K (3) 4000K (4)
LR1P724V30-04WTemp	Flat 007 profile.	30"	24-3/8" x 5/8" x 3/8" (619 mm x 15 mm x 10 mm)	4	211	3000K (3) 4000K (4)
LR1P724V33-05WTemp	Flat 007 profile.	33"	28-5/16" x 5/8" x 3/8" (719 mm x 15 mm x 10 mm)	5	242	3000K (3) 4000K (4)
LR1P724V36-05WTemp	Flat 007 profile.	36"	32-1/4" x 5/8" x 3/8" (819 mm x 15 mm x 10 mm)	5	258	3000K (3) 4000K (4)
LR1P724V39-05WTemp	Flat 007 profile.	39"	36-3/16" x 5/8" x 3/8" (919 mm x 15 mm x 10 mm)	5	290	3000K (3) 4000K (4)
LR1P724V42-06WTemp	Flat 007 profile.	42"	36-3/16" x 5/8" x 3/8" (919 mm x 15 mm x 10 mm)	6	305	3000K (3) 4000K (4)
LR1P724V45-06WTemp	Flat 007 profile.	45"	40-1/8" x 5/8" x 3/8" (1019 mm x 15 mm x 10 mm)	6	337	3000K (3) 4000K (4)
LR1P724V48-06WTemp	Flat 007 profile.	48"	44-1/16" x 5/8" x 3/8" (1119 mm x 15 mm x 10 mm)	6	353	3000K (3) 4000K (4)

**Blue indicates dealer choice. Temp indicates Kelvin Temperature.**

LR1P724V18-03W3 (Example part number for 24V Vivid Series, Flat 007 Profile for a 18" cabinet, Soft White 3000K Kelvin temperature)

## COMPATIBLE POWER SUPPLIES

PART NUMBER	DESCRIPTION	DIMENSIONS
T-24V-24W-PI	24 watt AC/DC 2 prong plug-in, 24 volt DC 1 AMP.	3-1/8" x 1-3/4" x 1-3/16" (79 mm x 44 mm x 31 mm)
T-24V-60W-PI	60 watt AC/DC 2 prong plug-in, 24 volt DC 2.5 AMP.	4-3/8" x 1-15/16" x 1-3/16" (111 mm x 49 mm x 30 mm)
T-24V-120W-PI	120 watt AC/DC 3 prong plug-in, 24 volt DC 5 AMP.	6-5/16" x 2-11/16" x 1-1/4" (161 mm x 68 mm x 33 mm)
T-24V-DT30W-HW	30 watt 24 volt DC dimmable class 2 LED hardwired.	13-13/16" x 3" x 1-1/2" (350 mm x 77 mm x 37 mm)
T-24V-DT60W-HW	60 watt 24 volt DC dimmable class 2 LED hardwired.	13-13/16" x 3" x 1-1/2" (350 mm x 77 mm x 37 mm)
T-24V-DT120W-HW	120 watt 24 volt DC dimmable class 2 LED hardwired.	15" x 3" x 2-1/4" (380 mm x 77 mm x 57 mm)
T-DQ75W-24V-HW	75 watt, 24 volt class 2 rated DC RF CV Hardwired Power Supply with built-in Wireless Receiver.	19-1/8" x 1-3/16" x 13/16" (486 mm x 31 mm x 21 mm)



# Linear Fixture Radiance Series

Flat Profile Linear Fixture



LED Tape Lighting  
**5 YEAR**  
WARRANTY

Accessories  
**3 YEAR**  
WARRANTY

## FEATURES

- 8 mm tape lighting pre-assembled in aluminum housing with frosted lens
- 18 diodes per foot
- Simple installation
- 90 CRI (Color Rendering Index – true color)
- No Ultraviolet (UV) or Infrared (IR)
- 30,000 hour LED life at 70% lumen maintenance
- 24-volt DC plug-in or hardwired power supply required (order separately)
- UL/cUL Listed
- Available in Soft White 3000K ([3](#)) or Cool White 4000K ([4](#))

## APPLICATIONS

- Under Cabinet
- Interior Cabinet
- Stairs
- Display Cases
- Toe Kick/Soffit
- Outdoor

## TECHNICAL INFORMATION

Series	24V Radiance Linear Fixture Series
Input Voltage	24-volt DC
Color Temperature (Kelvin)	Soft white 3000K ( <a href="#">30</a> ) Cool white 4000K ( <a href="#">40</a> )
CRI (Color Rendering Index)	90+
LED Type	SMD2835
Lumens	101 lumens per foot
Max Run	Refer to power supply specs
Dimmable	5% – 100%
Rating	UL/cUL Listed
Rated Life	30,000 hrs
LED Beam Angle	120°
LED Spacing	3/8"
Mounting	Mounting Clips and Screws (included)
Wiring	20/2 stranded
Operating Temperature	-4°F to 140°F (-20°C to 60°C)
Environment	Damp, Wet, Dry locations
Construction Material	Heat-resistant 8mm PCB, micro-waterproof spray silicone IP65 rated, extruded aluminum, polycarbonate (lens)
Warranty	5 years



## COMPATIBLE DIMMING SYSTEMS / SWITCHES

PART NUMBER	DESCRIPTION	DIMENSIONS
T-Q-1Z-WC-RF- <a href="#">Color</a>	Uno 1-Zone LED controller. On / Off / Dimmer. Use with LED Receiver.	2-5/8" x 1-5/16" x 3/8" (67 mm x 33 mm x 10 mm)
T-Q-2Z-WC-RF- <a href="#">Color</a>	Duo 2-Zone LED controller. On / Off / Dimmer. Use with LED Receiver.	2-5/8" x 1-5/16" x 3/8" (67 mm x 33 mm x 10 mm)
T-Q-4Z-WC-RF- <a href="#">Color</a>	Quattro 4-Zone LED controller. On / Off / Dimmer. Use with LED Receiver.	2-5/8" x 1-5/16" x 3/8" (67 mm x 33 mm x 10 mm)
T-TWAV-WR-120	WAV 120 watt smart LED Receiver. Use with a Wireless Controller.	4-1/4" x 2-1/4" x 3/8" (108 mm x 57 mm x 22 mm)
T-Q-WR96	96 watt LED Receiver. Use with a Wireless Controller.	3-7/8" x 1-13/16" x 13/16" (95 mm x 37 mm x 20 mm)
T-Q-WR240	240 watt LED Receiver. Use with a Wireless Controller.	7" x 1-13/16" x 7/8" (178 mm x 46 mm x 20 mm)
T-DSS-30W-IR	Infrared (IR) door sensor switch.	3/8" x 1" x 1-1/4" (10 mm x 25 mm x 32 mm)
T-2HDSS-30W-IR	Infrared (IR) door sensor switch <b>with two heads.</b>	3/8" x 1" x 1-1/4" (10 mm x 25 mm x 32 mm)
T-MSS-60W	Motion sensor switch.	1/2" x 2-1/4" (13 mm x 57 mm)
T-PSS-60W-IR	Infrared (IR) sensor proximity switch.	2-1/4" x 3/8" (57 mm x 10 mm)
T-TDS-60W	LED touch dimmer.	3/8" x 2" x 2" (10 mm x 51 mm x 51 mm)
T-WSS-60W-IR	Infrared (IR) wave sensor switch.	2-1/4" x 3/8" (57.15mm x 9.5 mm)
DVLV-600P- <a href="#">Color</a>	600W Diva slide dimmer.	4-11/16" x 2-15/16" x 1-5/16" (119 mm x 75 mm x 135 mm)
T-RS-BK	On / off round switch.	15/16" (24 mm)
T-WAV-AC120V-R	WAV 120 volt AC/AC Smart Receiver.	1-3/4" x 1-3/4" x 13/16" (44 mm x 44 mm x 21 mm)

## STRANDED WIRE

PART NUMBER	DESCRIPTION	OUTSIDE DIAMETER
T-CW20G-STR-25	25 ft. spool of 20/2 AWG 2 conductor, in-wall rated stranded wire.	1/8" (3 mm)
T-CW20G-STR-50	50 ft. spool of 20/2 AWG 2 conductor, in-wall rated stranded wire.	1/8" (3 mm)
T-CW20G-STR-100	100 ft. spool of 20/2 AWG 2 conductor, in-wall rated stranded wire.	1/8" (3 mm)
T-CW20G-STR-1	20/2 AWG 2 conductor, in-wall rated stranded wire. Specify the number of feet needed when ordering. Sold per foot. Must order a minimum of 2 ft.	1/8" (3 mm)



# Linear Fixture Accessories

Connectors and Additional Installation Components

Accessories  
**3 YEAR WARRANTY**

## CONNECTORS

PART NUMBER	DESCRIPTION	DIMENSIONS
T-MBC	Male barrel to conductor screw-down connector. Use to add a female barrel connector to a pair of lead wires for connection to an LED light power supply or cable.	1-9/16" x 9/16" x 1/2" (40 mm x 14 mm x 13 mm)
T-FBC	Female barrel to conductor screw-down connector. Use in conjunction with male barrel connector to pair lead wires or to connect and rewire an LED light power supply cable.	1-9/16" x 9/16" x 1/2" (39 mm x 14 mm x 13 mm)
T-MPC	Male Plug Connector. Connect to output side of receiver for easy plug-and-play system.	6-1/2" overall length (165 mm)
T-FPC	Female Plug Connector. Connect to input side of receiver or into a Male Plug Connector for easy connection.	6-1/2" overall length (165 mm)
T-EZWC	EZ wire-to-wire connector. Must strip wire to insert into connector. Use to daisy chain fixtures in parallel runs or to connect around corners.	13/16" x 11/16" x 5/16" (20 mm x 18 mm x 8 mm)
T-3WSP	DC 3-way splitter plug. Use to connect multiple LED light fixtures to a dimming system.	16" overall length (406 mm) 8" length of one splice (203 mm)
T-JB-W	Mini plastic junction box for wires – white.	

## ADDITIONAL (OPTIONAL) INSTALLATION COMPONENTS

PART NUMBER	DESCRIPTION	DIMENSIONS
T-AMP-180W	Use when powering more than 40 ft. of illuminaLED single color tape lighting or RGB multi-color tape lighting. An additional power supply will be needed to operate the amplifier. <b>NOTE:</b> Not compatible with TandemLED™ products.	7" x 1-13/16" x 7/8" (178 mm x 46 mm x 22 mm)
L-007-FR-48	007 flat aluminum housing 48" – Frosted (FR) lens. Compatible with illuminaLED 8 mm and 10 mm tape lighting for sturdy, dust-proof enclosure. This product is field-cuttable.	48" x 5/8" x 5/8" (1219 mm x 16 mm x 16 mm)
L-007-FR-90	007 flat aluminum housing 90" – Frosted (FR) lens. Compatible with illuminaLED 8 mm and 10 mm tape lighting for sturdy, dust-proof enclosure. This product is field-cuttable.	90" x 5/8" x 5/8" (2286 mm x 16 mm x 16 mm)

## MOUNTING CLIPS

PART NUMBER	DESCRIPTION	DIMENSIONS
L-MC-007	Mounting clip for L-007 aluminum housing – mounting screws included	5/8" wide (16 mm)

## DECORA COVER PLATES

PART NUMBER	DESCRIPTION	DIMENSIONS
T-DPL-Color	Decora style cover plate to fit over Wireless Controller on wall. Use with TandemLED smart controller (T-T-1Z-WC-RF- <a href="#">Color</a> ), Uno 1-Zone Controller (T-Q-1Z-WC-RF- <a href="#">Color</a> ), Duo 2-Zone Controller (T-Q-2Z-WC-RF- <a href="#">Color</a> ), Quattro 4-Zone Controller (T-Q-4Z-WC-RF- <a href="#">Color</a> ), or RGB Controller (T-C-RGBWC-RF- <a href="#">Color</a> ) to install on wall. Available in Almond ( <a href="#">AL</a> ), Black ( <a href="#">BK</a> ), Brown ( <a href="#">BR</a> ), Grey ( <a href="#">GR</a> ), or White ( <a href="#">WT</a> )	4-11/16" x 2-15/16" x 11/16" (119 mm x 75 mm x 17 mm)