

## Medium-Duty

100 lb. Load Class

1/2" Side Clearance

Max. Drawer Width: 24"



## 6400 Stainless Steel Drawer Slide

The 6400 Stainless Steel Drawer Slide is manufactured from 304 series grade stainless steel and uses a USDA H-1 approved grease.

### Applications

- Outdoor Cooking Areas
- Coastal Environments
- Watercraft

### Specifications

**Model:** 6400 Full Extension Stainless Steel Drawer Slide

**Mounting:** Side

**Disconnect:** Lever Release

**Hole Pattern:** 32mm and Traditional

**Face Frame Mounting:** Yes

**Type:** Ball-Bearing

**Travel:** Full Extension

**Finish:** Stainless Steel

**Length:** 10", 12", 14", 16", 18", 20", 22", 24", 26", 28"

**Clearance:** .50" + .03"-0" on each side

**Height:** 1.78" [45.2mm]

**Packaging:** Poly Pack: all sizes - 10 pair per carton

**Action:** Telescopic

**Slide Configuration:** Unhanded

### Rating

**Load:** 100 lb.

**Max. Drawer Width:** 24"

As with all Knappe & Vogt drawer slides, the 6400 is designed to meet or exceed ANSI performance standards as established by BIFMA, BHMA and KCMA.


### Hardware

#8 x 1/2" Stainless Steel Pan Head Screws (included)

### Warranty

Limited Lifetime Warranty


#### Profile



#### Clearance

1/2" + 1/32"-0"  
.50" + .03"-0"  
12.7mm + .3mm - 0mm

Charted Information



SKU Number*	Slide Size inch/mm	Length inch/mm	Travel inch/mm	A1 inch/mm	A inch/mm	B inch/mm	C inch/mm	D inch/mm	E inch/mm	F inch/mm	G inch/mm	H inch/mm
6400P SS 10	10" [250mm]	9.84" [250mm]	10" [ 254mm]	-	-	-	-	-	7.56" [192mm]	-	-	-
6400P SS 12	12" [300mm]	11.81" [300mm]	12" [305mm]	-	-	-	-	-	9.53" [242mm]	8.82" [224mm]	-	-
6400P SS 14	14" [350mm]	13.78" [350mm]	14" [356mm]	-	-	-	-	-	11.50" [292mm]	8.82" [224mm]	-	-
6400P SS 16	16" [400mm]	15.75" [400mm]	16" [406mm]	-	-	12.60" [320mm]	-	-	13.46" [342mm]	8.82" [224mm]	12.60" [320mm]	-
6400P SS 18	18" [450mm]	17.72" [450mm]	18" [457mm]	-	5.04" [128mm]	12.60" [320mm]	-	-	15.43" [392mm]	8.82" [224mm]	13.86" [352mm]	-
6400P SS 20	20" [500mm]	19.69" [500mm]	20" [508mm]	-	5.04" [128mm]	13.86" [352mm]	-	-	17.40" [442mm]	8.82" [224mm]	16.38" [416mm]	-
6400P SS 22	22" [550mm]	21.65" [550mm]	22" [559mm]	-	5.04" [128mm]	-	16.38" [416mm]	-	19.37" [492mm]	8.82" [224mm]	13.86" [352mm]	17.64" [448mm]
6400P SS 24	24" [600mm]	23.62" [600mm]	24" [610mm]	5.04" [128mm]	-	-	16.38" [416mm]	-	21.34" [542mm]	8.82" [224mm]	13.86" [352mm]	18.90" [480mm]
6400P SS 26	26" [650mm]	25.59" [650mm]	26" [660mm]	5.04" [128mm]	8.82" [224mm]	-	16.38" [416mm]	21.42" [544mm]	23.30" [592mm]	8.82" [224mm]	13.86" [352mm]	21.42" [544mm]
6400P SS 28	28" [700mm]	27.56" [700mm]	28" [711mm]	5.04" [128mm]	8.82" [224mm]	-	17.64" [448mm]	21.42" [544mm]	25.27" [642mm]	8.82" [224mm]	13.86" [352mm]	21.42" [544mm]

