

# HR Series Controls



## HRT-3 - Push Button Timer

- The HRT-3 model push button timer allows the homeowner control of the indoor humidity level in rooms where excess humidity is produced
- Press the button once the LED comes on then release, this activates the ventilation system to high speed for 20 minutes.
- Press the button until the LED blinks 2 times then release, this activates the ventilation system to high speed for 40 minutes.
- Press the button until the LED blinks 3 times then release, this activates the ventilation system to high speed for 60 minutes.
- Meets ASHRAE 62.2 continuous ventilation standards



## HRRD-1 - Dehumidistat

- The HRRD-1 allows the users to select the humidity level using the Relative Humidity Sensor Dial
- The Relative Humidity Sensor Dial will “click” when the dial reaches approximate level of relative humidity and overrides the ventilation system to high speed once the level of humidity is above the set point
- For best results install in bathrooms, kitchen and laundry room
- Meets ASHRAE 62.2 continuous ventilation standards



## HRRD-3P - Dehumidistat

- The HRRD-3P allows the users to select the humidity percentage, fan range and operation modes.
- Includes Relative Humidity Sensor, Speed Control Selector Switch and Mode Selector Switch
- The Relative Humidity Sensor Dial will “click” when the dial reaches approximate level of relative humidity and overrides the ventilation system to high speed once the level of humidity is above the set point
- Speed Control (OFF, NORMAL and REDUCED)
- Mode Control (INTERM and CONT)
- For best results install in bathrooms, kitchen and laundry room
- Meets ASHRAE 62.2 continuous ventilation standards



## FT247 - Programmable Fan Timer

- Provides 7 ON and 7 OFF events per day
- LCD display
- Rechargeable battery back-up
- Push button activation
- Meets ASHRAE 62.2 continuous ventilation standards
- **Note:** Do not use with fluorescent lamp ballasts