

SPECIFICATIONS DUCTLESS RANGE HOODS

= I Rinkin

• Dimensions

Overall bottom projection - 181/2" Overall top projection -12" Height - 6"

Available widths: 21", 24", 30" & 36"

Hood Body

23 gauge cold rolled steel, auto welded, coated with a baked enamel finish.

Motor

2 speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, 60 hz., 0.7 amps. Complete with 105°C lead wires.

Lighting

Single 60 watt cook light capacity (bulb not included).

Ducting Options

Ductless - combination grease/charcoal filter included. (Model RF55)

Fan Blade

One piece polymeric, electronically balanced blade. 61/8" diameter with 3 paddles.

Electrical connection

Hood top - 7/8" knockout hole for use with 1/2" cable clamp Hood back - 7/8" knockout hole for use with 1/2" cable clamp

Filters


UL rated, class 2 filter. Combo Grease/Charcoal: RF55 - 87/8"x103/8" (included).

Available Finishes

White, Biscuit, Almond, Black & Stainless Steel.







PROJECT							ARCHITECT		
LOCATION							ENGINEER		
CONTRACTOR							SUBMITTED BY		DATE
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS





Updated 5-12